

MATERIAL SAFETY DATA SHEET
InkSource
Ink
16-8420
1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product name	: 16-8420
Synonyms	: ; 26-8420
Material uses	: Industrial applications: Ink for use in a continuous ink jet process.
Emergency phone	: Medical: CALL RMPDC, USA (303) 623-5716 Transporters: CALL CHEMTREC, USA (800)-424-9300
Manufacturer	: Marconi Data Systems Inc., 1500 Mittel Boulevard, Wood Dale, IL, 60191-1073 U.S.A Phone: 1-800-843-3610 Fax: 1-800-582-1343 Marconi Data Systems Europe BV., Strijkviertel 39, 3454 PJ De Meern, The Netherlands. Phone: 31-030-6693000 Fax: 31-030-6693060


2. COMPOSITION / INFORMATION ON INGREDIENTS
Information on hazardous ingredients

<u>CAS No.</u>	<u>Percent (%)</u>	<u>Chemical name</u>
1) 141-78-6	1 - 3	Ethyl acetate
2) 64-17-5	13 - 20	Ethanol
3) 78-93-3	50 - 65	2-Butanone
4)	3 - 7	Colorant, Organometallic Compound, Chromium III
5) 67-63-0	1 - 3	Isopropyl alcohol
6) 9004-70-0	3 - 7	Nitrocellulose

* Occupational Exposure Limit(s), if available, are listed in section 8

3. HAZARDS IDENTIFICATION

National Fire Protection Association (U.S.A.) :


Emergency Overview

: **WARNING! FLAMMABLE LIQUID AND VAPOR. HARMFUL.** Keep away from flame, heat, and static discharge sources. Irritant and central nervous system depressant: Avoid inhalation of vapors and contact with eyes and skin. May be harmful or fatal if swallowed. If inhaled remove to fresh air. If splashed in eyes flush with water. If contacts skin flush with water and wash with mild soap. In medical emergency call Poison Control Center (USA 303-623-5716) and a physician. Read MSDS before using.

Effects and symptoms

<u>Chemical name</u>	<u>Effects and symptoms</u>
1) Ethyl acetate	May cause irritation of respiratory tract, coughing, shortness of breath. Slightly irritating to the skin. Absorbed through skin. Moderately irritating to the eyes. Inhalation and Ingestion : Can cause CNS depression. Can cause dizziness, lightheadedness, headache, nausea, and blurred vision. May cause loss of consciousness/coma . Repeated or prolonged contact with irritants may cause dermatitis. Defatting to the skin.
2) Ethanol	May cause irritation of respiratory tract, coughing, shortness of breath. Slightly irritating to the skin. Absorbed through skin. Moderately irritating to the eyes. Inhalation and ingestion may cause drowsiness, dizziness, incoordination and other effects of intoxication. May cause loss of consciousness/coma and death . Medical conditions aggravated by overexposure: liver kidneys gastro-intestinal tract respiratory system cardiovascular system and central nervous system .
3) 2-Butanone	Irritating to eyes and respiratory system. Defatting to the skin. Harmful by inhalation, in contact with skin and if swallowed. Can cause dizziness, lightheadedness, headache, nausea, and blurred vision. Can cause CNS depression.
4) Colorant, Organometallic	Slightly irritating to the skin. Slightly irritating to the eyes. Prolonged skin

Continued on Next Page

- Compound, Chromium III
5) Isopropyl alcohol
- contact may cause dermatitis with drying and cracking of skin. May cause irritation of respiratory tract, coughing, shortness of breath. Slightly irritating to the skin. Absorbed through skin. Moderately irritating to the eyes. Ingestion : Exposure can cause nausea, headache and vomiting. Inhalation and Ingestion : Can cause CNS depression. Can cause dizziness, lightheadedness, headache, nausea, and blurred vision. May cause loss of consciousness/coma and death . Repeated or prolonged contact with irritants may cause dermatitis.
- 6) Nitrocellulose
No known significant effects or critical hazards.

4. FIRST AID MEASURES

- Inhalation** : If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention if symptoms appear.
- Ingestion** : Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention if symptoms appear.
- Skin contact** : Wash with soap and water. Get medical attention if irritation develops.
- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Get medical attention.

5. FIRE-FIGHTING MEASURES

- Extinguishing media** : Flammable liquid, insoluble in water.
SMALL FIRE: Use DRY chemical powder.
LARGE FIRE: Use water spray or fog. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosion.
- Special fire-fighting procedures** : Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.
- Hazardous thermal decomposition products** : These products are carbon oxides (CO, CO₂). Some metallic oxides.
- Protection of fire-fighters** : Be sure to use an approved/certified respirator or equivalent.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions** : Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self-contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.
- Environmental precautions and clean-up methods** : Flammable liquid, insoluble in water.
Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not get water inside container. Do not touch spilled material. Prevent entry into sewers, basements or confined areas; dike if needed. Call for assistance on disposal.

7. HANDLING AND STORAGE

- Handling** : Keep locked up. Keep away from heat. Keep away from sources of ignition. Keep away from direct sunlight or strong incandescent light. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. Avoid shock and friction. Wear suitable protective clothing. If ingested, seek medical advice immediately and show the container or the label. Keep away from incompatibles such as oxidizing agents, reducing agents.
- Storage** : Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).
- Packaging materials** : Use original container.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- Engineering controls** : Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.
- Hygiene measures** : Wash hands after handling compounds and before eating, smoking, using lavatory, and at the end of day.
- Occupational Exposure Limits**

<u>Chemical name</u>	<u>Exposure limits</u>
1) Ethyl acetate	1) United States ACGIH TWA 8 hours 400 ppm 2) United States OSHA TWA 8 hours 400 ppm
2) Ethanol	1) United States ACGIH TWA 8 hours 1000 ppm 2) United States OSHA TWA 8 hours 1000 ppm
3) 2-Butanone	1) United States ACGIH STEL 15 minutes 300 ppm 2) United States ACGIH TWA 8 hours 200 ppm 3) United States OSHA TWA 8 hours 200 ppm
4) Colorant, Organometallic Compound, Chromium III	1) United States ACGIH TWA 8 hours 1 mg/m ³
5) Isopropyl alcohol	1) United States ACGIH TWA 8 hours 400 ppm 2) United States ACGIH STEL 15 minutes 500 ppm 3) United States OSHA TWA 8 hours 400 ppm
6) Nitrocellulose	No established limits.

Personal Protective Equipment

Respiratory system	: Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Wear appropriate respirator when ventilation is inadequate.
Skin and body	: Lab coat.
Hands	: Impervious gloves.
Eyes	: Splash goggles.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state and appearance	: Liquid.
Color	: Black
Odor threshold	: The highest known value is 100 ppm. Weighted average: 30 ppm.
Boiling point	: The lowest known value is 77 °C. Weighted average: 79 °C.
Melting point	: May start to solidify at -83 °C. Weighted average: -92 °C.
Specific gravity	: 0.86 (Water = 1)
Vapor density	: The highest known value is 3.0. The lowest known value is 1.6. (Air = 1)
Vapor pressure	: The highest known value is 73 mmHg at 20°C. Weighted average: 64 mmHg at 20°C.
Evaporation rate (butyl acetate = 1)	: The highest known value is 7.1. Weighted average: 5.8.
Solubility	: Easily soluble in methanol, diethyl ether, n-octanol, acetone. Insoluble in cold water, hot water.
Octanol/water partition coefficient	: The product is much more soluble in oil.
pH	: Not applicable.
Flash point	: -9 °C.
Autoignition temperature	: The lowest known value is 165 °C. Weighted average: 464 °C.
Flammable limits	: The lowest known value is 2.0%. The highest known value is 19.0%.
Volatility (w/w)	: 83 %.
VOC Volatility (w/w) - less exempt volatile.	: 83 %.

10. STABILITY AND REACTIVITY

Stability	: Unstable. (Nitrocellulose)
Conditions and materials to avoid	: Not available.
Hazardous reactions	: Reactive with oxidizing agents, reducing agents. Slightly reactive to reactive with acids, alkalis. The product may undergo hazardous decomposition, condensation or polymerization, it may react violently with water to emit toxic gases or it may become self-reactive under conditions of shock or increase in temperature or pressure.
Hazardous decomposition products	: These products are carbon oxides (CO, CO ₂). Some metallic oxides.

11. TOXICOLOGICAL INFORMATION

Chemical name	Toxicological Information
1) Ethyl acetate	1) LD50 Oral Rat: 5620 mg/kg 2) LD50 Oral Rabbit: 4935 mg/kg 3) LD50 Oral Mouse: 4100 mg/kg 4) LD50 Dermal Rabbit: 16000 mg/kg 5) LC50 Inhalation vapor Mouse: 45000 mg/m ³ 2 hours
2) Ethanol	1) LD50 Oral Rat: 7060 mg/kg 2) LD50 Oral Mouse: 3450 mg/kg 3) LD50 Oral Rabbit: 6300 mg/kg 4) LC50 Inhalation vapor Rat: 20000 ppm 10 hours 5) LCLo Inhalation vapor Dog: 5500 ppm hours 6) LCLo Inhalation vapor Guinea pig: 21900 ppm hours
3) 2-Butanone	1) LD50 Oral Rat: 2737 mg/kg 2) LD50 Oral Mouse: 2190 mg/kg 3) LD50 Oral Mouse: 4050 mg/kg 4) LD50 Dermal Rabbit: 6480 mg/kg 5) LC50 Inhalation vapor Rat: 23500 mg/m ³ 8 hours 6) LCLo Inhalation vapor Female. Rat Fetotoxicity and developmental abnormalities (homeostasis) in rats.: 1000 ppm 1 hours
4) Colorant, Organometallic Compound, Chromium III	1) LD50 Oral Rat: 2000 mg/kg 2) LD50 Dermal Rabbit: 2000 mg/kg
5) Isopropyl alcohol	1) LD50 Oral Rat: 5045 mg/kg 2) LD50 Oral Rabbit: 6410 mg/kg 3) LD50 Oral Mouse: 3600 mg/kg 4) LD50 Dermal Rabbit: 12800 mg/kg
6) Nitrocellulose	1) LD50 Oral Rat: 5000 mg/kg 2) LD50 Oral Mouse: 5000 mg/kg

12. ECOLOGICAL INFORMATION

Persistence/degradability	: Not available.
Ecotoxicity	: Not available.
Heavy Metals	: Total concentration: Pb, Hg, Cd, Cr(VI) < 100 ppm
California, VOC Content	: 719 grams volatile organic / liter less water or exempt volatile.

13. DISPOSAL CONSIDERATIONS

Disposal methods	: Waste must be disposed of in accordance with federal, state and local environmental control regulations.
RCRA waste code	: Not available.

14. TRANSPORT INFORMATION

UN number	: UN1210
Proper shipping name	: Printing Ink
TDG classification	: 3
Packing group	: II

15. REGULATORY INFORMATION

CERCLA	: The following product(s) is (are) listed by CERCLA: Ethyl acetate (1 - 3%) ; 2-Butanone (50 - 65%) ; Colorant, Organometallic Compound, Chromium III (3 - 7%)
SARA 313	: The following product(s) is (are) listed on SARA 313: 2-Butanone (50 - 65%) ; Colorant, Organometallic Compound, Chromium III (3 - 7%)
California prop. 65	: This product contains the following ingredients for which the State of California has found to cause cancer, birth defects or other reproductive harm, which would require a warning under the statute: Toluene (<= 0.0004%)

16. OTHER INFORMATION

Date of issue : September 17, 2001
Prepared by : Garth Studebaker, CSP
Version : 2.13

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.