



MATERIAL SAFETY DATA SHEET
Ethanol Solvent
300-4004-001

SECTION I - PREPARATION INFORMATION

Product Name Ethanol Solvent
Product Code 300-4004-001
Emergency Phone contact CHEMTREC at (800) 424-9300

Original document date: 05/05

Date of revisions: 00/00

SECTION II - IDENTIFICATION

Product Name Ethanol Solvent
Product Use Ink Jet Printers
Description Clear liquid with solvent odor

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM (HMIS)

HAZARD RATINGS: 0 Minimal 1 Slight 2 Moderate 3 Serious 4 Extreme B Hand & Eye Protection
HEALTH 1 FLAMMABILITY 3 REACTIVITY 0 PERSONAL PROTECTION B

NOTICE: These ratings are for general rapid interpretation. The end-user is responsible for determining the proper protective procedures.

SECTION III - HAZARDOUS INGREDIENTS

Ingredient	CAS#	%	TLV*	PEL*	LD₅₀** (g/kg)	LC₅₀** (g/m³ per 8hr)
Ethanol	64-17-5	60 - 100	1000	1000	7.0	20,000ppm/10h
Isopropanol	67-63-0	1 - 5	400	400	5.04	12,000ppm/ 8hr
Acetone	67-64-1	1 - 5	750	750	5.8	50,100mg/m ³

SECTION IV - PHYSICAL DATA

Boiling Range 78° C
Melting Range -130° C
Freezing Range -130° C
Vapor Pressure 44 mm of Hg @ 20° C
Vapor Density (Air=1) Greater than air
Solubility In Water Miscible
Solubility In Organic Solvents Miscible
Specific Gravity (Water=1) 0.791
Percent Volatile By Volume (%) 100%
Evaporation Rate (N-Butyl Acetate=1) 1.9
pH in concentrate Not Applicable
pH in dilution as used Not Applicable
Appearance And Odor Clear liquid with solvent odor
Odor Threshold Not Available

SECTION V - FIRE AND EXPLOSION HAZARD

Flash Point (Tcc)

18° C

Auto Ignition Temperature	422° C
Upper Flammable Limit (%By Vol.)	19
Lower Flammable Limit (%By Vol.)	3.3
Hazardous Combustion Products	Carbon Monoxide, Carbon Dioxide
Extinguishing Media	Regular foam or dry chemical
Explosion Data (Sensitive To Mechanical Impact)	No
Explosion Data (Sensitive To Static Discharge)	Yes

FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus with full facepiece operated in the positive pressure demand mode.

SECTION VI - REACTIVE DATA

Condition Of Instability	None Known
Incompatibility	Strong oxidizing agents
Conditions Of Reactivity	Not applicable
Hazardous Decomposition Products	Carbon Monoxide, Carbon Dioxide

SECTION VII - TOXICOLOGICAL PROPERTIES (HEALTH HAZARD)

ROUTES OF ENTRY: Skin contact, skin absorption, ingestion, inhalation, and eyes

EFFECT OF ACUTE EXPOSURE:

Eyes	May cause extreme eye irritation. Symptoms may include burning, tearing, redness, swelling and eye damage.
Skin	Exposure may cause skin irritation. Prolonged or repeated exposure may dry the skin. Symptoms may include redness, burning, drying, cracking, and skin damage.
Breathing	Excessive inhalation of vapors can cause nasal and respiratory irritation. Central nervous system effects include dizziness, weakness, fatigue, nausea, headache, possible unconsciousness and even death. Inhalation of material into the lungs can cause chemical pneumonitis, which can be fatal.
Swallowing	Can cause gastrointestinal irritation, nausea, vomiting, diarrhea, blindness and death.
Exposure Limits	See section III
Sensitization To Product	Not Available
Carcinogenicity	Not Available
Reproductive Toxicity	Not Available
Teratogenicity	Not Available
Mutagenicity	Not Available
Toxicological Synergistic Products	None known

EFFECTS OF CHRONIC EXPOSURE:

Ethanol - Nausea, vomiting, flushing, mental excitement or depression, drowsiness, impaired perception, uncoordination, stupor, coma and death may occur.

Acetone - A skin and severe eye irritant. Experimental reproductive effects. Narcotic in high concentration.

Isopropanol - Ingestion or inhalation of large quantities of vapor may cause flushing, headache, dizziness, mental depression, nausea, vomiting, narcosis, anesthesia, coma and death.

SECTION VIII - PREVENTATIVE MEASURES

PERSONAL PROTECTION:

Respiratory protection	If workplace exposure limit(s) of product or any other component is exceeded, a NIOSH/OSHA approved respirator is advised. (See your safety
-------------------------------	---

	equipment supplier for specific details.)
Ventilation	Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below PEL/ TLV.
Protective gloves	Wear chemical resistant gloves. (Consult your safety equipment supplier.)
Eye protection	Wear chemical splash goggles in compliance with OSHA regulations. However, OSHA regulations also permit other types of safety glasses.
Other protective equipment	Wear impervious clothing and boots to prevent prolonged exposure.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Keep away all sources of ignition from spill. If spill is indoors, ventilate areas of spill and soak up the spill with absorbent material. Do not let spilled or leaking material enter watercourse.

DISPOSAL METHOD: Absorb in vermiculite, floor absorbent or other absorbent material and dispose in licensed facility. Observe all federal, state and local regulations.

HANDLING AND STORAGE: Protect from freezing. Overheating may cause container to rupture. Covered storage is preferable.

SPECIAL SHIPPING INFORMATION: SEE SECTION X

SECTION IX - FIRST AID MEASURES

Oral Ingestion	Seek immediate medical attention.
Eye Contact	Flush with water for 15 minutes and seek medical attention.
Skin Contact	Wash with soap and water. Wash contaminated clothing before reuse.
Skin Absorption	If skin irritation persists, seek medical attention.
Inhalation	Remove to fresh air, give artificial respiration and seek medical attention.
Effects Of Overexposure	May cause headaches if inhaled. Seek medical attention. If swallowed, can cause drunken-type behavior followed by severe systemic illness.

SECTION X - TRANSPORTATION

DOT / TDG Proper Shipping Name	UN1210 Printing Ink Related Material
DOT / TDG Hazard Class	3
DOT / TDG Label	Flammable Liquid

SECTION XI - DISCLAIMER

All information, recommendations, and suggestions appearing herein concerning this product are based upon data obtained from the manufacturer and/or recognized technical sources; however, Citronix makes no warranty, representation, or guarantee as to the accuracy, sufficiency, or completeness of the material set forth herein. It is the user's responsibility to determine the safety, toxicity and suitability of his/her own use, handling and disposal of the product. Additional product literature may be available upon request. Since actual use by others is beyond our control, no warranty, express or implied, is made by Citronix as to the effects of such use, the results to be obtained or the safety and toxicity of the product, nor does Citronix assume any liability arising out of use by others of the product referred to herein. The data in this Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

*NIOSH Publication #94-116 **Sax's Dangerous Properties of Industrial Mtls. 10th Ed.